



KVM Series

AC/DC Kilovoltmeters

■ The HIPOTRONICS KVM Series of kilovoltmeters are highly accurate, portable voltage measurement systems traceable to NIST standards. The KVM series consists of a high voltage divider assembly, a precision readout device, durable carrying case and interconnection leads. The carrying case and battery operation make the system completely portable for field testing while the precision divider assembly and readout device make it suitable for laboratory use.



FEATURES

- ☑ **Perform multiple measurements**
 - DC
 - Ripple Voltage – AC superimposed on DC
 - AC Peak
 - AC Absolute average
- ☑ **Low temperature and voltage coefficients**
- ☑ **Digital readout**
- ☑ **AC and DC coupling**
- ☑ **Battery or line power operation**
- ☑ **Light weight and portable divider**
- ☑ **Rugged, reinforced carrying case**
- ☑ **True divider**

BENEFITS

Suitable for use - in the field, factory, or lab settings

Simple to use – unit can be used with oscilloscopes or other measuring devices

Time Saving – fast and accurate measurements under varying ambient conditions

NIST traceable – significant cost savings on outside calibrations

FEATURES

KVM Series AC/DC Kilovoltmeters are ideal for testing and calibrating:

- ➔ AC/DC Hipot testers
 - ➔ High Voltage DC power supplies
 - ➔ Semiconductor implantation systems
-

TECHNICAL SPECIFICATIONS

Model No.	KVM100	KVM200	KVM300	KVM400	
DISPLAY FEATURES					
INSTRUMENT	Digital, 3 1/2 Digits 1/2" LED, Auto Polarity				
HIGH RANGE (kV)	0-100	0-199	0-300	0-400	
LOW RANGE (kV)	0-10.0	0-19.9	0-30.0	0-40.0	
ACCURACY (DC)	<0.5%	All Accuracies as % of full scale, range from 10-100% of scale			
(rms, average)	<1.0%				
(peak)	<2.0%				
INPUT	Impedance= 1M; Level= 100VFS				
POWER REQUIREMENTS	Internal Battery - 4 NiCd Cells, Size D 8 Hours Operation - 16 Hour Recharge (at 120V or 220V) External Operation - 115, 60Hz or 220V, 50Hz				
HIGH VOLTAGE DIVIDER ASSEMBLIES					
VOLTAGE RATING (DC, kV)	100	200	300	400	
(AC, rms, average, kV)	100	200	300	400	
(peak, kVp)	142	283	425	566	
NOMINAL RATIO (VOUT/VIN)	Assuming a Load Impedance of 1M & <500pF				
	1000:1	2000:1	3000:1	4000:1	
HV ARM IMPEDANCE	Parallel R&C Branches				
	RESISTANCE (MΩ)	380	760	900	1520
	CAPACITANCE (pF)	200	200	200	200
FREQUENCY RESPONSE	DC to 1kHz				
STABILITY COEFFICIENTS	<0.025%/°C <0.1% over the working voltage range				
TEMPERATURE VOLTAGE					
INTERCONNECT CABLES	*One 25 coaxial (RG58/U) with BNC type connectors for interconnection between divider and readout device *One 15' braided cable for divider ground lead *One 6' Detachable Power Supply Cord				

Ordering Information

System

Above Model # with Suffix "-DO" indicates the divider section only of the kilovoltmeter **KVM###-***

* Designate input voltage. 'A' for 120Vin or 'B' for 220Vin.

Options:

-SPARE PARTS KITS – Catalog nos. SPK1-(Model No.)

European, Asia, South & Central America, Australia
Haefely Test AG
 Birsstrasse 300
 4052 Basel
 Switzerland
 ☎ + 41 61 373 4111
 📠 + 41 61 373 4912
 🌐 sales@haefely.com

China (Sales & Service Office)
Haefely Test AG – Beijing Office
 8-1-602, Fortune Street
 No. 67, Chaoyang Road, Chaoyang District
 Beijing, 100025
 P. R. China
 ☎ + 86 10 8578 8099
 📠 + 86 10 8578 9908
 🌐 sales@haefely.com.cn

USA Contact
Hipotronics Inc.
 1650 Route 22
 PO Box 414
 Brewster, NY 10509
 USA
 ☎ + 1 845 279 8091
 📠 + 1 845 279 2467
 🌐 sales@hipotronics.com